

IN THE SPECIFICATION:

Please amend Page 2 below the bottom line thereof to amend the previously added following paragraphs:

--A process for the production of a six layer composite material (1, 21) with ~~a~~ only one plastic layer (4, 24) that has release properties with respect to adhesive consisting of

locating materials producing the release properties within the plastic layer, wherein a first web (2, 22) is provided in production of the composite material (1, 21) on one side of which ~~a~~ only one layer of adhesive (3, 23) is located, and said only one adhesive layer is always coextruded and directly bonded together with ~~the~~ said only one plastic layer (4, 24) with the release properties, which is in turn directly bonded to a second web (5, 25); and

wherein said first web and said second web is selected from the group consisting of paper, metal foil, and non-woven fabric; and

providing the first web and the second web in a spaced apart position; and extruding ~~the~~ said only one adhesive layer (3, 23) and ~~the~~ said only one layer (4, 24) with the release properties between the two webs (2, 22 and 5, 25); and forming the bond directly with the two webs;

wherein further layers (26) are provided that are located on and directly bonded to both sides of the web (2, 5 or 22, 25), such

that both webs are each provided with a further layer (26) directly bonded to the webs.--

--A process for the production of a six layer composite material (1, 21) with ~~a~~ only one plastic layer (4, 24) that has release properties with respect to adhesives consisting of

locating materials producing the release properties within the plastic layer, wherein a first web (2, 22) is provided in production of the composite material (1, 21) on one side of which ~~a~~ only one layer of adhesive (3, 23) is located, and said only one adhesive layer is always coextruded and directly bonded together with ~~the~~ said only one plastic layer (4, 24) with the release properties, which is in turn directly bonded to a second web (5, 25); and

wherein said first web and said second web is selected from the group consisting of paper, metal foil, and non-woven fabric; and

wherein further layers (26) are provided that are located on and directly bonded to both sides of the webs (2, 5 or 22, 25), such that both webs are each provided with a further layer (26) directly bonded to the webs.--

--The drawings illustrate the fact that the layers are directly bonded together and are directly bonded to the webs, and

that there is only one adhesive layer and there is only one plastic layer with release properties.--